PEAD-SM SERIES

Type				Inverter Heat Pump						
Indoor Unit				PEAD-SM71JA (L)	PEAD-SM100JA (L)	PEAD-SM100JA (L)	PEAD-SM125JA (L)	PEAD-SM125JA (L)	PEAD-SM140JA (L)	PEAD-SM140JA (L)
Outdoor Unit				SUZ-SM71VA	PUZ-SM100VKA	PUZ-SM100YKA	PUZ-SM125VKA	PUZ-SM125YKA	PUZ-SM140VKA	PUZ-SM140YKA
Refrigerant				R32(*1)						
Power Supply	Source			Outdoor power supply						
	Outdoor (V / Phase / Hz)			VA · VKA:230 / Single / 50, YKA:400 / Three / 50						
Cooling	Capacity	Rated	kW	7,1	9,5	9,5	12,1		13,4	
		Min-Max	kW	2,2-8,1	4,0-10,6	4,0-10,6	6,0-13,0		6,1-14,1	
	Total Input	Rated	kW	2,08	2,95	2,95	4,17		4,96	
	EER			3,41	3,21	3,21	2,9		2,7	
	EEL Rank			-	-	-	-		-	
	Design load		kW	7,1	9,5	9,5	12,1		13,4	
	Annual electricity consumption (*2)		kWh/a	451	626	626	-		-	
	SEER			5,5	5,3	5,3	-		-	
	Energy efficiency class			A	A	A	-		-	
Heating (Average Season)	Capacity	Rated	kW	8	11,2	11,2	13,5		15	
		Min-Max	kW	2,0-10,2	2,8-12,5	2,8-12,5	4,1-15,0		4,2-15,8	
	Total Input	Rated	kW	2,21	3,02	3,02	3,85		4,28	
	COP			3,61	3,7	3,7	3,5		3,5	
	EEL Rank			-	-	-	-		-	
	Design load		kW	5,8	8	8	8,5		9,4	
	Declared Capacity	at reference design temperature	kW	5,2 (-6°C)	6,0 (-10°C)	6,0 (-10°C)	8,5 (-10°C)		9,4 (-10°C)	
		at bivalent temperature	kW	5,2 (-7°C)	7,0 (-7°C)	7,0 (-7°C)	8,5 (-10°C)		9,4 (-10°C)	
		at operation limit temperature	kW	5,2 (-10°C)	4,5 (-15°C)	4,5 (-15°C)	6,0 (-15°C)		7,0 (-15°C)	
	Back up heating capacity		kW	0,6	2	2	0		0	
	Annual electricity consumption (*2)		kWh/a	2080	2865	2865	-		-	
	SCOP			3,9	3,9	3,9	-		-	
	Energy efficiency class			A	A	A	-		-	
Operating Current (Max)			A	16,8	22,7	14,2	29,3	14,3	32,8	14,3
Indoor Unit	Input (cooling/heating)	Rated	kW	0,17 / 0,15	0,25 (0,23) / 0,23	0,25 (0,23) / 0,23	0,36 (0,34) / 0,34	0,36 (0,34) / 0,34	0,39 (0,37) / 0,37	0,39 (0,37) / 0,37
	Operating Current (Max)		A	1,97	2,65	2,65	2,76	2,76	2,78	2,78
	Dimensions	HxWxD	mm	250-1100-732	250-1400-732	250-1400-732	250-1400-732	250-1400-732	250-1600-732	250-1600-732
	Weight (L:No Draln Pump)		kg	30 (29)	39 (38)	39 (38)	40 (39)	40 (39)	44 (43)	44 (43)
	Air Volume (Lo-Mid-Hi)		m³/min	17,5-21,0-25,0	24,0-29,0-34,0	24,0-29,0-34,0	29,5-35,5-42,0	29,5-35,5-42,0	32,0-39,0-46,0	32,0-39,0-46,0
	External Static Pressure		Pa	35 / 50 / 70 / 100						
	Sound Level (Lo-Mid-Hi) (SPL)		dB(A)	26-30-34	29-34-38		33-36-40		34-38-43	
	Sound Level (PWL)		dB(A)	58	62		66		67	
Outdoor Unit	Dimensions	HxWxD	mm	880x840x330		981x1050x330 (+40)				
	Weight		kg	55	76	78	84	85	84	85
	Air Volume	Cooling	m³/min	50,1	79	79	86	86	86	86
		Heating	m³/min	50,1	79	79	92	92	92	92
	Sound Level (SPL)	Cooling	dB(A)	49	51	51	54	54	55	55
		Heating	dB(A)	51	54	54	56	56	57	57
	Sound Level (PWL)	Cooling	dB(A)	66	70	70	72	72	73	73
	Operating Current (Max)		A	14,8	20	11,5	26,5	11,5	30	11,5
	Breaker Size		A	20	32	16	32	16	40	16
Ext. Piping	Diameter	Liquid/Gas	mm	9,52 / 15,88						
	Max. Length	Out-In	m	30			40			
	Max. Height	Out-In	m	30						
Guaranteed Operating Range (Outdoor)		Cooling(*3)	℃	-15 ~ +46						
		Heating	℃	-10 ~ +24	-15 ~ +21					
Refrigerant/GWP				R32/675(*4)						
Pre-Charged quantity		Weight	kg	1,45	3,10	3,10	3,60	3,60	3,60	3,60
		CO_2 equivalent	t	0,98	2,09	2,09	2,43	2,43	2,43	2,43
Max added quantity		Weight	kg	2,37	4,10	4,10	5,00	5,00	5,00	5,00
		CO_2 equivalent	t	1,60	2,77	2,77	3,38	3,38	3,38	3,38

(*1) Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, If leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO 2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.
(*2) Energy consumption based on standard test results.Actual energy consumption will depend on how the appliance is used and where it is located.
(*3) Optional air protection guide is required where ambient temperature is lower than -5°C.
(*4) This GWP value is based on Regulation(EU) No 517/2014 from IPCC 4th edition,