

## Technical specifications

MODEL			PMFY-P20VBM-E	PMFY-P25VBM-E	PMFY-P32VBM-E	PMFY-P40VBM-E	
Power	Single phase, 220-240V 50Hz						
Capacity in cooling mode*1	kW		2,2	2,8	3,6	4,5	
	Btu/h		7500	9600	12300	15400	
Capacity in heating mode*1	kW		2,5	3,2	4,0	5,0	
	Btu/h		8500	10900	13600	17100	
Power consumption	Cooling	kW	0,042	0,044	0,044	0,054	
	Heating	kW	0,042	0,044	0,044	0,054	
Current	Cooling	A	0,20	0,21	0,21	0,26	
	Heating	A	0,20	0,21	0,21	0,26	
External finish	Unit	Galvanized steel plate					
	Grille	Nr. Munsel 0.98Y 8.99/0.63					
Dimensions AxLxP	Unit	mm	230x812x395	230x812x395	230x812x395	230x812x395	
	Grille	mm	30x1000x470	30x1000x470	30x1000x470	30x1000x470	
Net weight	Unit	kg	14	14	14	14	
	Grille	kg	3	3	3	3	
Heat exchanger	Cross fin						
Fan	Type x Quantity		Linear Flow fan x 1				
	Air flow*2	m³/min	6,5-7,2-8,0-8,7	7,3-8,0-8,6-9,3	7,3-8,0-8,6-9,3	7,7-8,7-9,7-10,7	
		l/s	108-120-133-145	122-133-143-155	122-133-143-155	128-145-162-178	
		cfm	230-254-283-307	258-283-304-328	258-283-304-328	272-307-343-378	
	Ext. Static pressure	Pa	0	0	0	0	
Motor	Type		Single-phase induction motor				
	Ext. Static pressure	kW	0,028	0,028	0,028	0,028	
Air filter	Polypropylen honeycomb (long life)						
Refrigerant pipe diameter	Gas (swaged)	mm	ø12,7	ø12,7	ø12,7	ø12,7	
	Liquid (swaged)	mm	ø6,35	ø6,35	ø6,35	ø6,35	
Local drain pipe diameter		mm	O.D. 26	O.D. 26	O.D. 26	O.D. 26	
Sound pressure*2*3		dB(A)	27-30-33-35	32-34-36-37	32-34-36-37	33-35-37-39	

\*1 The heating/cooling capacity indicates the maximum values during operation under the following conditions.

Cooling: indoor 27°C (81 °F) DB/19°C(66°F) WB, outdoor 35°C (95°F) DB. Heating: indoor 20°C (68°F) DB, outdoor 7°C (45°F) DB/6°C (43° F) WB.

\*2 Airflow rate/noise levels are expressed as (low-middle1-middle2-high).

\*3 Measured in an anechoic chamber.