MSZ-S SERIES

DC Inverter

Indoor Unit



MSZ-SF15/20VA

Outdoor Unit

For MXZ Connection Only

Remote Controller



Econo Cool | Pure White | AUTO VANE | SWING | AUTO | i save | ACO | Auto Restart | Centralised On/Off (Optional) | Group Control (Optional) | M-NET connection (Optional) | MXZ connection | Flare connection | Self Diagnosis | Failure Recall

Type				Inverter Heat Pump	
Indoor Unit				MSZ-SF15VA	MSZ-SF20VA
Outdoor Unit				N/A*2	N/A*2
Power Supply	**Source**			Outdoor power supply	
	Outdoor (V/Phase/Hz)			230 / Single / 50	
Cooling	**Capacity**	Rated	kW	-	-
		Min - Max	kW	-	-
	Total Input	Rated	kW	-	-
	EER			-	-
		EEL Rank		-	-
	SPL	Indoor Unit [Silent-Lo-Mid-Hi-SHi*1]	dB(A)	21 - 26 - 30 - 35 - 40	21 - 26 - 30 - 35 - 42
		Outdoor Unit [Rated]	dB(A)	-	-
	Air Volume	Indoor Unit [Silent-Lo-Mid-Hi-SHi*1]	m^3/min	3.5 - 3.9 - 4.6 - 5.5 - 6.4	3.5 - 3.9 - 4.6 - 5.5 - 6.9
		Outdoor Unit [Rated]	m^3/min	-	-
Heating	**Capacity**	Rated	kW	-	-
		Min - Max	kW	-	-
	Total Input	Rated	kW	-	-
	COP			-	-
		EEL Rank		-	-
	SPL	Indoor Unit [Silent-Lo-Mid-Hi-SHi*1]	dB(A)	21 - 26 - 30 - 35 - 40	21 - 26 - 30 - 35 - 42
		Outdoor Unit [Rated]	dB(A)	-	-
	Air Volume	Indoor Unit [Silent-Lo-Mid-Hi-SHi*1]	m^3/min	3.7 - 4.4 - 5.0 - 6.0 - 6.8	3.7 - 4.4 - 5.0 - 6.0 - 7.3
		Outdoor Unit [Rated]	m^3/min	-	-
Operating Current (max)				-	-
Indoor Unit	**Input**	Rated	kW	0.017	0.019
	Operating Current (max)		A	0.17	0.19
	Dimensions	H x W x D	mm	250 - 760 - 168	250 - 760 - 168
	Weight		kg	7.7	7.7
	Breaker Size		A	-	-
Outdoor Unit	**Dimensions**	H x W x D	mm	-	-
	Weight		kg	-	-
	Operating Current (max)		A	-	-
	Breaker Size		A	-	-
Ext. Piping	**Diameter**	Liquid / Gas	mm	6.35 / 9.52	6.35 / 9.52
	Max. Length	Out-In	m	-	-
	Max. Height	Out-In	m	-	-
Guaranteed Operating Range (Outdoor)		Cooling	℃	-	-
		Heating	℃	-	-

*1 SHi → Super High *2 MSZ-S is for MXZ connection only.